

# EXPERIMENTAL ASSESSMENT OF THE CONTINUOUS PNEUMATIC CLASSIFICATION PROCESS OF SUGARCANE BAGASSE

Olivares, E.G.1; Cortez, L.A.B.2; Roca, G.A.A.3; Almeida, E.4

1 - Laboratório Nacional de Ciência e Tecnologia do Bioetanol – CTBE, Brasil, 2 - Faculdade de Engenharia Agrícola – FEAGRI, Universidade Estadual de Campinas – UNICAMP, Brasil; 3 - Centro de Estudios de Eficiencia Energética - CEEFE, Universidad de Oriente, Santiago de Cuba, Cuba; 4 - Faculdade de Engenharia Química – FEQ, Universidade Estadual de Campinas-UNICAMP, Brasil

## Introduction

It is presented a new technological concept for the handling and treatment of solid particulate of biomass from sugarcane mills mainly sugarcane bagasse, which consisted through project development, construction, assembly and operation of an experimental installation in pilot plant scale to carry out the continuous pneumatic classification process of sugarcane bagasse, separating this biomass in three well-defined fractions, within certain controlled ranges of flow of bagasse and classification agent (air), called fine, medium and coarse.

In a first moment was performed the calculations that allowed the development of the pneumatic classification equipment. The calculations were based on physical and fluid-dynamics sugarcane bagasse properties, as well as constructive criteria, scale relations, project and operational parameters.

The operate principle of the pneumatic classifier is based on solid particles fluidization, elutriation and pneumatic transport principles within an air column. The fine particles are dragged and collected in a cyclone at the top of the equipment, the medium particles circulating in the column are collected through an opening next to the middle of this and the coarse particles, heavy enough to not be either dragged or put into lifting, fall by gravity action into an opening at the end lower of the air column. The feeding of the equipment is carried out by a rotative valve, projected to operate between 5 to 30kg/h with nominal value considered of 20kg/h. The air flow obtained into the column is produced by a centrifugal fan.

In a subsequent step was defined a set of basic experiments planned taking account three physical conditions of the sugarcane bagasse, obtained before feeding the classifier equipment. The physical conditions were sugarcane bagasse at equilibrium moisture (8% to 10% wet basis), bagasse at 50% moisture (condition of the bagasse used in Brazilian sugarcane mills boilers), and milled bagasse at equilibrium moisture with particle diameter size control at milling process of 5 and 10mm.

The experiments were divided in two blocks, in first one, integral sugarcane bagasse at equilibrium moisture was used in order to study the pneumatic classifying in a special condition that excluded the bagasse moisture effect. Thus, it was elaborated an experimental design at two levels, varying bagasse feeding rate and air flow, with a middle point and three replicates of this.

In the case of the second block of experiments were studied milled bagasse and bagasse at 50% of moisture. The planning chosen taking account to fix the feeding rate factor and to vary the classification agent rate factor. This is the traditional experimental design type with a change at each time.

## **Results and conclusions**

The analysis of the first experiments block showed that higher rates were obtained independent of the bagasse feeding. About the air flow this varies causes higher or lower on classified fraction dispersion. To fine fraction the particle dispersion was low to the three air flow used, approximately 0,750mm to particle mean diameter, but when more increased the air flow more varied the particle diameter in the fraction, for example, using air flow of 108m<sup>3</sup>/h (higher value) was observed lower dispersion with particles diameters varying between 0,130 to 0,750mm.

With respect medium fraction the lower degree of dispersion was observed when the air flow were 88 (mean value) and 108m<sup>3</sup>/h respectively, observing 75% of mass fraction of classified bagasse with particle diameter greater than 0,380mm and 80% of mass fraction of classified bagasse with particle diameter greater than 0,750mm respectively. To coarse fraction the lower dispersion was obtained when 108m<sup>3</sup>/h air flow was applied with 60% of mass fraction of classified bagasse with particle diameter greater than 9,08mm.

The experimental results of the second block of experiments showed that it is possible to pneumatically classify sugarcane bagasse with 50% of moisture content (wet basis). It was observed that the separation of the coarse, medium and fine fractions, for all tested samples, in both cases of sugarcane bagasse at 50% moisture and milled sugarcane bagasse, there was a repeatable aerodynamic behavior. It is noticed that in the case of previously milling of the sugarcane bagasse, it was possible to classify into more homogeneous fractions with respect to the moisture and less moisture bagasse (50% and at equilibrium moisture respectively). The explanation for this behavior is based on the fact that milling itself is a process of pre-homogenization.

Likewise, it was shown that the dispersion of sizes in each separated fraction depends on the diameter of each fraction and operation conditions of the classifier. It was observed an increase in the dispersion (heterogeneity) with the increase of the average diameter of the fraction. Thus, the heterogeneity of the separated fractions increases from the fine to the coarse one. It was also observed that the air flow shows a determining factor for controlling the degree of dispersion of particle sizes in the different fractions of bagasse.

These results are significantly important considering that in some technological processes which use polydisperse biomass as raw material, especially biochemical processes of conversion, the physical homogeneity of the material, based on the distribution of sizes and shapes of particles, in addition to its inorganic material content, are necessary criteria to achieve a high performance and energy efficiency in the processes.

*Supported by FAPESP – Fundação de Amparo à Pesquisa do Estado de São Paulo, Brazil*

## **Author publications:**

### **Edgardo Olivares Gómez**

1 - Rogério César de Cerqueira Leite (coordenador) . Bioetanol Combustível: uma Oportunidade para o Brasil. 1. ed. Brasília, Brasil: Centro de Gestão em Estudos Estratégicos - CGEE, 2009. v. 01. 536 p.

2 - CORTEZ, L. A. B. ; LORA, E. E. S. ; GÓMEZ, E. O. . Biomassa para Energia. 2. ed. Campinas: Editora da UNICAMP, 2010. v. 1. 736 p.

3 - Santos, W.D. ; GÓMEZ, E. O. ; Buckeridge, M.S. Part I - Chapter 2 - Bioenergy and the Sustainable Revolution. In: M.S. Buckeridge and G.H. Goldman. (Org.). Routes to Cellulosic Ethanol. 01 ed. New York: Springer Science+Business Media, LLC, 2011, v. 01, p. 15-26.

4 - GÓMEZ, E. O.; Souza, R.T.G.; ROCHA, G. J. M.; ALMEIDA, E.; CORTEZ, L. A. B. A palha de cana-de-açúcar como matéria prima para processos de segunda geração. In: Luis Augusto Barbosa Cortez. (Org.). Bioetanol da cana-de-açúcar: P&D para produtividade e sustentabilidade. Campinas: Edgard Blucher, 2010, 992p.

5 - GÓMEZ, E. O.; Souza, R.T.G.; ROCHA, G. J. M.; ALMEIDA, E.; CORTEZ, L. A. B. THE SUGARCANE TRASH AS FEEDSTOCK FOR THE SECOND GENERATION PROCESSES. In: Luis Augusto Barbosa Cortez. (Org.). SUGARCANE BIOETHANOL - R&D FOR PRODUCTIVITY AND SUSTAINABILITY. 01 ed., Editora Edgard Blucher Ltda., 2010.

6 - Souza-Corrêa, J.A. ; Pimenta, M.T.B. ; ROCHA, G. J. M. ; GÓMEZ, E. O. ; SQUINA, F. M. ; Curvelo, A.A.S. ; Filho, J.A. . Hydrothermal and Atmospheric Pressure Microplasma Pretreatment Processes of Sugarcane Bagasse. In: Elena Tatarova; Vasco Guerra; Evgenia Benova; Andre Ricard. (Org.). Plasma for Environmental Issues (Proceedings of the 2nd International Workshop at the 36th European Physical Society Conference on Plasma Physics, July 02-03, 2009, in Sofia, Bulgaria). 01 ed. Sofia, 2010, p. 68-76.

7 - ROCHA, G. J. M.; Barbosa, M.T.B.P.; GÓMEZ, E. O.; Oliveira, B.R.; Rezende, C.C.; Driemeier, C.E.; Correa, J.A.S.; Filho, J.A.; Rossell, C.E.V. . PRÉ-TRATAMENTOS FÍSICO-QUÍMICOS DO BAGAÇO DE CANA-DE-AÇÚCAR PARA HIDRÓLISE ENZIMÁTICA. ALCOOLBras, São Paulo, Brasil, 30 abr. 2010.

8 - ROCHA, G. J. M.; Gonçalves, A.R.; Oliveira, B.R.; GÓMEZ, E. O.; Rossell, C.E.V. COMPOSITIONAL VARIABILITY OF RAW, STEAM EXPLODED AND DELIGNIFICATED SUGARCANE BAGASSE. In: 8º Congresso sobre Geração Distribuída e Energia no Meio Rural, 2010, Campinas, São Paulo, Brasil. Anais do 8º Congresso sobre Geração Distribuída e Energia no Meio Rural, 2010.

9 - GÓMEZ, E. O.; ROCA, G.A.A.; CORTEZ, L. A. B.; ALMEIDA, E.; OLIVEIRA, B.R.; ROCHA, G. J. M. Estudo experimental da classificação pneumática contínua de bagaço de cana-de-açúcar. In: 8º Congresso sobre Geração Distribuída e Energia no Meio Rural - AGRENER 2010, 2010, Campinas, São Paulo, Brasil. Anais do 8º Congresso sobre Geração Distribuída e Energia no Meio Rural - AGRENER 2010, 2010.

10 - SQUINA, F. M.; PRADE, R. A.; MURAKAMI, M. T.; GÓMEZ, E. O.; PRADELLA, J. G. C.; Rossell, C.E.V. Development of a Library for Biomass-Conversion Enzymes. In: XVII SIMPÓSIO NACIONAL DE BIOPROCESSOS, 2009, Natal/RN. ANAIS DO XVII SIMPÓSIO NACIONAL DE BIOPROCESSOS, 2009.

11 - BORGES, R. A.; Squina, F.; GÓMEZ, E. O.; Rossell, C.E.V.; PRADELLA, J. G. C. Análise por Microscopia Eletrônica de Varredura da Desconstrução de Fibra de Bagaço de Cana-de-Açúcar tratada com Enzima Celulolítica Comercial. In: XVII SIMPÓSIO NACIONAL DE BIOPROCESSOS, 2009, NATAL/RN. ANAIS DO XVII SIMPÓSIO NACIONAL DE BIOPROCESSOS, 2009.

12 - ULLMANN, M.A.; SANTOS, L.V.; PIMENTEL, V.L.; Filho, J.A.; ROCHA, G. J. M.; GÓMEZ, E. O.; MEDEIROS-RIBEIRO, G.; ZERI, A.C.. ISOLAMENTO E VISUALIZAÇÃO POR AFM DE MICROFIBRAS NANOESTRUTURADAS DO RESÍDUO PROCESSADO DE *Saccharum Officinarum* L.. In: 19o RAU - Reunião Anual de Usuários do LNLS - Laboratório Nacional de Luz Síncrotron, 2009, Campinas, São Paulo, Brasil. Livro de Resumos, 2009.

13 - Rossell, C.E.V.; PRADELLA, J. G. C.; GÓMEZ, E. O.; SQUINA, F. M. Physical Conditioning Unit of the Sugarcane Biomass Feedstock: Sugarcane Bagasse and Sugarcane Trash. In: Workshop on Hydrolysis Route for Cellulosic Ethanol from Sugarcane, 2009, Campinas. Workshop on Hydrolysis Route for Cellulosic Ethanol from Sugarcane, 2009.

### **Eduardo de Almeida**

1 - GÓMEZ, Edgardo Olivares; SOUZA, Renata Torres; ROCHA, George Jackson de Moraes; ALMEIDA, Eduardo; CORTEZ, Luís Augusto Barbosa. A palha de cana-de-açúcar como matéria-prima para processos de segunda geração. In: CORTEZ, L. A. B. (Organizador). **Bioetanol de Cana-de-Açúcar**. São Paulo, SP: Editora Blucher, 2010, 992p.

2 - GÓMEZ , Edgardo Olivares; ALARCÓN, Guillermo Alfonso Roca; CORTEZ, Luís Augusto Barbosa; ALMEIDA, Eduardo; OLIVEIRA, Bruno Rodrigues; ROCHA, George Jackson de Moraes. **Estudo experimental da classificação pneumática contínua de bagaço de cana-de-açúcar**. Publicação nos anais do 8º Congresso Internacional sobre Geração Distribuída e Energia no Meio Rural – AGRENER GD 2010. Campinas, SP.

This document was created with Win2PDF available at <http://www.win2pdf.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.  
This page will not be added after purchasing Win2PDF.